

FITTING GUIDE

Corner Post

FI.PK.FIT.011 - CURVED/SQUARE CNR POST OR PILASTER ACCESSORIES



(J) x8 L Bracket Small




(B) x16 5/8" Screws



(H) x4 1 1/4" Screws



PROTECT AGAINST DAMAGE



Step 1.

Scribe/cut the back of the decor end panel to the wall. If the height requires cutting/scribing ensure it is done on the top edge.



Include the size of the post in your measurements so that it aligns with the frontals.

When cutting the decor end panel a table or circular saw is recommended.

BEFORE YOU START

INSTALLATION SHOULD BE PERFORMED BY A COMPETENT PERSON ONLY.


THIS PRODUCT COULD BE DANGEROUS IF INCORRECTLY INSTALLED.



Step 2.

If required, cut the post from the top to the required height.

See customer kitchen plan for reference.




Sample Post Shown

Step 3.



Fit 4 x L brackets SML (J) on the front edge of the decor end panel and then attach to the post using the 5/8" screws (B) provided, 2 per bracket.

Ensure decor end panel sits flush with post.



Step 4.

Fix filler panel to rear of decor end panel using 4 x L brackets SML (J) and the 5/8" screws (B) provided.





Base installation shown for illustration purposes.

Step 5.

Attach the assembled decor end panel to the carcass with 2 x 1 1/4" screws (H) from inside of the unit, through to the post. Then use 2 x 1 1/4" screws (H) from inside of the unit, through to the filler panel.

The screws should be equally spaced and positioned so they are least visible.



wren
KITCHENS